



Consumer Information Card
ENERGY CONTROL, INC. — Ossian, Indiana

Revised 6/7/07
 Code: 3814P

The Manufacturer recommends that Energy Control Cellulose Insulation be installed in accordance with each of the following chart minimums to provide the thermal resistance (R-Values) listed.

PNEUMATIC APPLICATION RECOMMENDATIONS — *ECI II Cellulose Insulation (25# Bag)

	R-Value @ 75°	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Framing: 2x6 @ 16 in. OC		Framing: None
				Maximum Net Coverage (ft ² /bag)	Bags Per 1000 ft ²	Minimum Weight (lbs/ft ²)
ATTIC	13	4.3	3.9	80.6	12.4	0.34
	19	6.0	5.4	50.6	19.8	0.55
	22	6.9	6.2	42.0	23.8	0.65
	23	7.2	6.4	39.8	25.1	0.68
	30	8.3	7.5	32.7	30.6	0.82
	35	9.2	8.2	28.8	34.7	0.93
	38	10.6	9.5	24.0	41.6	1.10
	40	11.4	10.3	21.9	45.7	1.20
	42	12.0	10.8	20.6	48.5	1.27
	46	12.6	11.3	19.5	51.3	1.34
	49	13.8	12.4	17.6	56.8	1.48
	54	14.6	13.2	16.4	61.0	1.59
	55	14.9	13.4	16.0	62.4	1.62
	57	16.1	14.5	14.7	67.9	1.76
60	16.3	14.7	14.4	69.3	1.80	
SIDE WALL	13.3	3.5	3.5	This bag will cover 36.4 sq.ft. in 2x4 closed sidewall		
	21	5.5	5.5	This bag will cover 22.7 sq.ft. in 2x6 closed sidewall		

BUILDER'S AND APPLICATOR'S CERTIFICATION

This is to certify that Energy Control Insulation has been installed in conformance with the above specifications to provide a thermal resistance of R-_____ using _____ bags of ECI 25# bags to cover _____ square feet of living area, and R-_____ using _____ bags to cover _____ square feet of garage ceiling. BAG DATE _____

 Date Company Name Applicator's Signature

 Date Company Name Builder's Signature

Energy Control, Inc. Cellulose Insulation Complies with Federal Specifications HH-1-515D & ASTM 739-03.

All heat sources including (but not limited to) recessed lights, fireplace, furnace and water heater flues have been wrapped in such a way as to prevent cellulose insulation from coming in contact with metal flue or light.

_____ (signature)