



**Consumer Information Card**  
**ENERGY CONTROL, INC. — Ossian, Indiana**

Revised 6/7/07  
 Code: 37514P

The Manufacturer recommends that Forest-Wool Cellulose Insulation be installed in accordance with each of the following chart minimums to provide the thermal resistance (R-Values) listed.

**PNEUMATIC APPLICATION RECOMMENDATIONS — Forest-Wool Insulation (25# Bag)**

	R-Value @ 75°	Initial Installed Thickness (in.)	Minimum Settled Thickness (in.)	Framing: 2x6 @ 16 in. OC		Framing: None
				Maximum Net Coverage (ft <sup>2</sup> /bag)	Bags Per 1000 ft <sup>2</sup>	Minimum Weight (lbs./ft <sup>3</sup> )
ATTIC	13	4.2	3.8	79.8	12.5	0.35
	19	5.9	5.3	49.8	20.1	0.55
	22	6.8	6.1	41.4	24.2	0.66
	23	7.1	6.4	39.1	25.5	0.69
	27	8.2	7.4	32.1	31.1	0.84
	30	9.1	8.2	28.3	35.3	0.94
	35	10.5	9.5	23.6	42.4	1.12
	38	11.4	10.3	21.4	46.6	1.23
	40	12.0	10.8	20.2	49.5	1.30
	42	12.6	11.3	19.1	52.3	1.37
	46	13.7	12.4	17.3	58.0	1.51
	49	14.6	13.1	16.1	62.2	1.62
	50	14.9	13.4	15.7	63.6	1.65
	54	16.1	14.4	14.4	69.3	1.80
	55	16.3	14.7	14.1	70.8	1.83
	57	16.9	15.2	13.6	73.6	1.90
60	17.8	16.0	12.8	77.9	2.01	
SIDE WALL	13.3	3.5	3.5	<i>This bag will cover 36.4 sq.ft. in 2x4 closed sidewall</i>		
	21	5.5	5.5	<i>This bag will cover 22.7 sq.ft. in 2x6 closed sidewall</i>		

**BUILDER'S AND APPLICATOR'S CERTIFICATION**

This is to certify that Forest-Wool brand Cellulose Insulation has been installed in conformance with the above specifications to provide a thermal resistance of R-\_\_\_\_\_ using \_\_\_\_\_ bags of FW 25# bags to cover \_\_\_\_\_ square feet of living area, and R-\_\_\_\_\_ using \_\_\_\_\_ bags to cover \_\_\_\_\_ square feet of garage ceiling. BAG DATE \_\_\_\_\_

\_\_\_\_\_  
 Date Company Name Applicator's Signature

\_\_\_\_\_  
 Date Company Name Builder's Signature

Forest-Wool Insulation Complies with Federal Specifications HH-1-515D & ASTM C-739-03 and ASTM C1374.

All heat sources including (but not limited to) recessed lights, fireplace, furnace and water heater flues have been wrapped in such a way as to prevent cellulose insulation from coming in contact with metal flue or light.

\_\_\_\_\_ (signature)